

Item		ZING C8	ZING C10	ZING C15E	ZING C20
Weight and Size	Net Weight	Approx. 17.4 lbs (7.9 kg)	Approx. 17.9 lbs (8.1 kg)	Approx. 23.4 lbs (10.6 kg)	
	Length × Width × Height	Approx. 31.5 × 13.7 × 33.4 in (800 × 350 × 850 mm)	Approx. 31.5 × 15.7 × 37.4 in (800 × 400 × 950 mm)	Approx. 36.2 × 15.7 × 40.2 in (920 × 400 × 1020 mm)	
Rider Requirement	Payload	44–110 lbs (20–50 kg)			
	Recommended Age	6–12 yrs.	8–14 yrs.	10+ yrs.	
	Recommended Height	3'9"–4'9" (115–145 cm)	4'3"–5'3" (130–160 cm)	4'7"–5'10" (140–180 cm)	
Vehicle Parameters	Max. speed	Approx. 10 mph (16 km/h)			
	Typical Range ⁽¹⁾	Approx. 6.2 miles (10 km)		Approx. 12.4 miles (20 km)	
	Traversable Terrain	Flat surface, paved road; obstacles < 0.4 in (1 cm); gaps < 1.2 in (3 cm)			
	Operating Temperature	14–104°F (-10–40°C)			
	Storage Temperature	-4–122°F (-20–50°C); 41–86°F (5–30°C) recommended			
	IP Rating	IPX4			
	Charging time	Approx. 3 h		Approx. 6 h	
Battery Pack	Battery Type	Lithium-ion battery			
	Nominal Voltage	21.6 V \approx			
	Charging Temperature	32–113°F (0–45°C); 50–95°F (10–35°C) recommended			
	Nominal Capacity / Energy	2500 mAh / 54 Wh		5000 mAh / 108 Wh	
	Battery Management System	Over-heating, short circuit, over-current and over-charge protection			
Motor	Nominal Power	120 W (0.12 kW)		150 W (0.15 kW)	
	Max. Power	180 W (0.18 kW)		260 W (0.26 kW)	
Battery Charger	Input Voltage	100–240 V~			
	Max. Output Voltage	25.2 V \approx			
	Rated Output	24.2 V \approx 1.0 A			
	Output Power	24.2 W (0.02 kW)			
Others	Braking Method	Hand-operated brake			
	Tires	Solid tire; material: synthetic rubber			
	Frame Material	Steel			
	Handlebar Material	TPR			
	Foot Pad Material	Sandpaper	Silicone		