

|         | Item                               | Parameter   |                             |
|---------|------------------------------------|---|-----------------------------|
| Product | Name                               | Ninebot KickScooter E2  | Ninebot KickScooter E2 Plus |
|         | Model                              | 051401U   | 051402U                     |
|         | Length × Width × Height            | Approx. 42.1 × 17.5 × 44.9 in (1070 × 445 × 1140 mm)                                    |                             |
|         | Folded: Length × Width × Height    | Approx. 42.1 × 17.5 × 19.8 in (1070 × 445 × 504 mm)                                     |                             |
|         | Net Weight                         | Approx. 33.1 lbs (15 kg)  | Approx. 33.7 lbs (15.3 kg)  |
| Rider   | Max. Payload                       | 198 lbs (90 kg)   |                             |
|         | Recommended Age                    | 14+   |                             |
|         | Required Height                    | 4'3"-6'2" (130-190 cm)  |                             |
| Machine | Max. Speed                         | Approx. 12.4 mph (20 km/h)  | Approx. 15.5 mph (25 km/h)  |
|         | Theoretical Range <sup>[1]</sup>   | Approx. 15.5 miles (25 km)  |                             |
|         | Range at Max. Speed <sup>[2]</sup> | Approx. 12.4 miles (20 km)  |                             |
|         | Max. Slope                         | Approx. 12%   |                             |
|         | Traversable Terrain                | Mostly smooth roads or normal asphalt, tarmac roads                                     |                             |
|         | Operating Temperature              | 14-104°F (-10-40°C)   |                             |
|         | Storage Temperature                | 14-122°F (-10-50°C)   |                             |
|         | IP Rating                          | IPX4  |                             |
|         | Duration of Charging               | Approx. 7.5 h   |                             |
| Battery | Nominal Voltage                    | 21.6 V <sub>DC</sub>  |                             |
|         | Max. Charging Voltage              | 25.2 V <sub>DC</sub>  |                             |
|         | Charging Temperature               | 32-111°F (0°C-44°C)   |                             |
|         | Nominal Energy                     | 220 Wh  |                             |
|         | Nominal Capacity                   | 10.2 Ah   |                             |
|         | Battery Management System          | Protection against overvoltage/undervoltage/short circuit/over-current/over temperature |                             |
| Motor   | Nominal Power                      | 0.25 kW, 250 W  | 0.3 kW, 300 W               |
|         | Max. power                         | 0.45 kW, 450 W  | 0.5 kW, 500 W               |
| Charger | Model                              | NBW25D201D5N-US   |                             |
|         | Output Power                       | 36.3 W  |                             |
|         | Input Voltage                      | 100-240 V~ 50-60 Hz   |                             |
|         | Max. Output Voltage                | 25.2 V <sub>DC</sub>  |                             |
|         | Rated Output                       | 24.2 V <sub>DC</sub> 1.5 A  |                             |
| Tire    | Tires                              | 8.1-inch inner hollow shock-absorbing tires   |                             |