

	Items	Parameter	
Product Info	Name	Segway SuperScooter GTS	
	Model	060203PC	
	L × W × H	Approx. 54.1×26.8×54.2 in (1375×680×1377 mm)	
	L × W × H (folded)	Approx. 54.1×26.8×27.6 in (1375×680×700 mm)	
	Net Weight	Approx. 87.1 lbs (39.5 kg)	
Riding Requirements	Max. Payload	330 lbs (150 kg)	
	Recommended Age	18—60 years old	
	Required Height	5.3—6.6 ft (160—200 cm)	
Vehicle Performance	Wheelbase	40.9 in (1040 mm)	
	Ground Clearance	7.2 in (183 mm)	
	Drive System	Rear-wheel Drive	
	Max. Speed ⁽¹⁾	Approx. 31 mph (50 km/h)	
	Ranges of Speed Modes ⁽²⁾	ECO	Approx. 45 miles (73.4 km)
		SPORT	Approx. 25 miles (40 km)
		RACE	Approx. 25 miles (40 km)
	Max. Slope	Approx. 30%	
	Traversable Terrain	Asphalt/flat pavement; obstacles < 1.2 in (3 cm); gaps < 1.2 in (3 cm)	
	Operating Temperature	14—104°F (-10—40°C)	
	Ambient Temperature For Storage	-4—122°F (-20—50°C)	
IP Rating	IPX6		
Charging Duration	230 VAC/25°C: Approx. 5.5h 115 VAC/25°C: Approx. 6.5h		
Battery Pack	Nominal Voltage	46.8 V	
	Max. Charging Voltage	54.6 V	
	Nominal Energy	899 Wh	
	Nominal Capacity	19.2 Ah	
	Charging Ambient Temperature	32—113°F (0—45°C)	
	Battery Management System	Overcharge Protection, Overheat Protection, Overdischarge Protection, Short Circuit Protection, and Overcurrent Protection	
Motor	Motor Type	Rear-drive Hub Motor	
	Nominal Power	1200 W	
	Max. Power	2400 W	

07

EN

	Items	Parameter
Charger	Model	NBW54D401D3D01
	Input Voltage	100—240 V-50—60 Hz
	Max. Output	53.6 V ≈ 3.9 A
	Nominal Output	53.6 V ≈ 1.3 A
	Rated Output Power	70 W
Tire	Tire Type	11-inch Self-sealing Tubeless Tires
	Tire Pressure	42—48 psi
	Material	Rubber
Others	Suspension System	Front: Twin-tube Hydraulic Shock Absorber
		Rear: Tailg-arm Hydraulic Shock Absorber
	Brake System	Front: Disc brake
		Rear: Disc brake