



**Product Specification**
**WOLF WARRIOR GT II**

Wolf Warrior GT / Wolf King GT - EN 17128 CLASS 2			
Version name	Wolf Warrior GT pro	Wolf Warrior GT pro	Wolf King GT pro
Configuration	60V35Ah *		72V55Ah*
Color			
Product Category	EN 17128 CLASS 2		
Battery Capacity	LG M50L/Jamung S0E 21700		
Motor	1200W*2		2000W*2
Max Speed	≤1KM/H		≤1KM/H
Max Range	150KM(75kg load, 25 km/h flat road ride at constant speed, full of electricity, sufficient air pressure)		180KM(75kg load, 25 km/h flat road ride at constant speed, full of electricity, sufficient air pressure)
Climbing Angle	≤45		≤50
Max Load	150KG		
Charger	67.2V2A 1+3 (2 pin)		80V1.5A 1+3 (2 pin)
Charging time (use 2A*)	About 8.8 hrs (use 2A2)		About 11.6 hrs (use 1.5A*2)
Charging time (use 2A*2)	About 4.3 hrs (use 4A+4A)		About 7hrs (use 2.5A+2.5A)
Shock Absorber	Front patent hydraulic shock absorber+Rear Cpring shock absorber		
Brake	Front and rear hydraulic brake (160) +ABS		
Light System/Item	Front and rear turn lights Driving Light LED Chassis light+LED front spotlight		
Controller	Motorcycle grade horn		
Open Size	(sine wave)60V 40A*2	Minimotors 60V 40A*2	(sine wave)72V 50A*2
Folding Size	1260x660x1250mm		1260x750x1300mm

N.W	50KG5		52KG5
G.W	54KG5		59KG5
Types	18 inch vacuum off-road tire/street tire 250R/pa		
Display	TFT Display	Minimotors EY3	TFT Display Minimotors EY3
Literature Certificates	IPX5 CE(E)MC MD LV05 ROHS FCC		
Product Material	handle, frame, bar material 6061-16 aluminum alloy and 6082-16 aluminum forging. Cover pp, Shaft iron445.		
<b>Upgrade point from the previous generation :</b>			
1. Higher waterproof grade, IPX5			
2. Add front and rear turn lights and driving lights.			
3. Adding an electronic control box, battery, and electronic control system separation, the cables will be simpler, more convenient for after-sale, the capacity of waterproof will be better.			
4. Controller current increases to 50A, motor maximum power increases to 8400W.			
5. Sine wave configuration, add TFT large screen display, new UI design (more beautiful, intelligent), all kinds of working state can be displayed. Internal parameters: front and rear power, front and rear start torque can be adjusted by itself. Front and rear motor power, temperature monitoring, can 30V user driving mode.			
6. Double model and ECD mechanical switch to add light to indicate working state.			
7.WOLF KING GT handle and shock absorber rod lengthened, more suitable for European and American people riding.			

\*The specification can be changed by manufacturer without notice to improve the quality and safety for users.

\*The distance can be affected by loaded weight, wind direct (wind speed), road condition, slope and the condition.