

|                            |  |   |       |                   |        |
|----------------------------|--|---|-------|-------------------|--------|
| Product                    | Name                                   | NAVEE Electric Scooter  |       |                   |        |
|                            | Model                                  | V25-E   | V25-D | V25i-E            | V25i-D |
| Dimensions                 | Vehicle: L x W x H (mm) [1]            | 1140 x 485 x 1165   |       | 1140 x 570 x 1165 |        |
|                            | After Folding: L x W x H (mm)          | 1140 x 160 x 505  |       | 1180 x 160 x 505  |        |
| Net Weight                 | Vehicle Net Weight (kg)                | 17.1  |       |                   |        |
| Rider                      | Load Range (kg)                        | 25-100  |       |                   |        |
|                            | Age (years)                            | 16 - 50   |       |                   |        |
|                            | Body Length (cm)                       | 120 - 200   |       |                   |        |
| Assembled Electric Scooter | Max. Speed (km/h)                      | 25  | 20    | 25                | 20     |
|                            | General Range (km) [2]                 | Approx. 25  |       |                   |        |
|                            | Max. Climbing Angle (%)                | Approx. 15  |       |                   |        |
|                            | Suitable Surfaces                      | Cement or asphalt road, with benches of less than 1 cm or crevices narrower than 3 cm |       |                   |        |
|                            | Operating Temperature (°C)             | -10 to 40   |       |                   |        |
|                            | Storage Temperature (°C)               | -20 to 45   |       |                   |        |
|                            | IP Rating                              | IPX5  |       |                   |        |
|                            | Charging Time (h)                      | Approx. 4-4.5   |       |                   |        |
| Battery Pack               | Model                                  | T2314-BA2A  |       |                   |        |
|                            | Nominal Voltage (VDC)                  | 36  |       |                   |        |
|                            | Max. Charge Voltage (VDC)              | 42  |       |                   |        |
|                            | Rated Energy (Wh)                      | 183.6   |       |                   |        |
|                            | Intelligent Battery Management System  | Over-heating, short circuit, over-current, over-discharge, and over-charge protection |       |                   |        |
|                            | Normal Charging Temperature Range (°C) | 0 to 40   |       |                   |        |
|                            | Rated Capacity (Ah)                    | 5.1   |       |                   |        |
| Wheel Motor                | Rated Power (kW; W)                    | 0.3; 300  |       |                   |        |
| Battery Charger            | Model [3]                              | LI-0554200130NA   |       |                   |        |
|                            | Output Power (kW; W)                   | 0.0533; 53.3  |       |                   |        |
|                            | Input Voltage (VAC)                    | 100-240 V~ 50-60 Hz   |       |                   |        |
|                            | Max. Output Voltage (VDC)              | 42.0  |       |                   |        |
|                            | Rated Output (VDC; A)                  | 41.0; 1.3   |       |                   |        |
| Tire                       | Front & Back Tires                     | 10-inch pneumatic tires   |       |                   |        |
| Bluetooth                  | Frequency Band (s)                     | 2.4000 - 2.4835 GHz   |       |                   |        |
|                            | Max. RF Power (dBm)                    | 8   |       |                   |        |